

VILLAGE OF GLENWOOD

SIDEWALK SPECIFICATIONS

1. Requirements for permit:

- A. The owner must submit a current copy of the plat of survey with the exact location of the sidewalk drawn on it and show all dimensions of entire project.
- B. The contractor must be licensed in the Village of Glenwood.
- C. The total cost of the job needs to be listed on the permit application.

2. Removal of existing sidewalk:

All existing sidewalk concrete shall be removed to the sub-base soil. Care shall be taken to protect any neighboring property when removing the existing sidewalk. It shall be the responsibility of the contractor to repair or replace any damage done to any adjoining property.

All concrete must be removed from the jobsite by the contractor.

3. Location:

- A. All sidewalks must be the proper distance from the street.

4. Specifications:

- A. Black dirt shall be dug out a minimum of 6 inches. Stone shall not be placed on any black dirt; it shall be placed on virgin clay.
- B. The site shall be inspected before the stone mix is installed, but after the removal of the black dirt.
- C. A second inspection shall be made after a minimum of 4 inches of CA6 stone mix is installed and compacted.
- D. Concrete sidewalks shall be a minimum of five feet (60 inches) wide and have a minimum of 5 bag mix five (5) inches thick with a sub-base of four (4) inches of compacted stone.
- E. The sidewalks shall have control joints cut every five feet (60 inches) and expansion joints as needed.
- F. The sidewalks shall have a minimum of two (2) #4 rebar continuous, evenly spaced and elevated into the center of the slab.

The Village of Glenwood Building Department is open Monday thru Friday from 9:00 am till 5:00pm, if you have any questions or to schedule an inspection please call (708) 753-2416.

A 24 hour advance notice has to be given for any inspection.
